

Camera

Embedded Network Server for Easy Deployment Better Al Video Analytics, Face Detection, People Counting via Al Deep Learning 5G Wireless Communication with Higher Bandwidth, Higher Mobility, Higher Scalability, Lower Latency

Megapixel Image Sensor 1/2.8" Progressive Scan CMOS 1/1.8" Progressive Scan CMOS 5.3~64mm, 12X Optical Zoom 8~32mm, 4X Optical Zoom Camera Lens H61°~H5°/D69°~D5°/V36°~V2° H44°~H13°/D51°~D15°/V25°~V7° Field of View Max.Image Resolution 1920x1080 3840x2160 SX1302, 8 Channels (Half/Full-duplex) Chipset 2 × Internal Antennas + 2 × 50 Ω N-Female External Connectors Antenna LoRaWAN® CN470/IN865/EU868/RU864/US915/AU915/KR920/AS923-1&2&3&4 Frequency Protocol V1.0 Class A/Class B/Class C and V1.0.2 Class A/Class B/Class C Cellular Support 5G/4G/3G (1 x Nano SIM) 1*RJ45 10M/100M Ethernet Port Connectivity Audio I/O Alarm I/O PoE (802.3at) / DC 12V±10% Power Supply Ingress Protection IP67(Only for Camera Body) Physical Characteristics 320 x 134 x 126 mm (12.60 x 5.28 x 4.96 in) Dimension 320 x 134 x 292 mm (12.60 x 5.28 x 11.50 in) (With 5G Antennas)